

Table 3 Piston Rod End Styles (Series H, LH and A) See page 105 for Series MN

ROD MM	A	B -.001 -.003	C	CC	*D	KK ₁	KK ₂ 3 5	NA	AD	AE +.001 -.002	AF diameter	AC
5/8	3/4	1 1/8	3/8	3/8-18	1/2	1/2-20	7/16-20	1 9/32	3/8	1/4	3/8	1 1/8
1	1 1/8	1 1/2	1/2	1-14	7/8	7/8-14	3/4-16	2 1/32	1 9/16	3/8	1 1/16	1 1/2 (#1)
1 1/8	1 5/8	2	5/8	1 3/8-12	1 1/8	1 1/4-12	1-14	1 11/32	1 1/16	3/8	7/8	1 3/4
1 1/4	2	2 3/8	3/4	1 3/4-12	1 1/2	1 1/2-12	1 1/4-12	1 49/64	1 9/16	1/2	1 1/8	2
2	2 1/4	2 5/8	7/8	2-12	1 11/16	1 3/4-12	1 1/2-12	1 61/64	1 11/16	5/8	1 3/8	2 5/8
2 1/2	3	3 3/8	1	2 1/2-12	2 1/16	2 1/4-12	1 5/8-12	2 29/64	1 19/16	3/4	1 3/4	3 1/4
3	3 1/2	3 3/4	1	3-12	2 5/8	2 3/4-12	2 1/4-12	2 15/16	2 7/16	7/8	2 1/4	3 5/8 (#2)
3 1/2	3 1/2	4 1/4	1	3 1/2-12	3	3 1/4-12	2 5/8-12	3 1/16	2 11/16	1	2 1/2	4 3/8
4	4	4 3/4	1	4-12	3 3/8	3 3/4-12	3-12	3 15/16	2 11/16	1	3	4 1/2
4 1/2	4 1/2	5 1/4	1	4 1/2-12	**	4 1/4-12	3 3/4-12	4 27/64	3 3/16	1 1/2	3 1/2	5 1/4
5	5	5 3/4	1	5-12	**	4 3/4-12	3 5/8-12	4 29/64	3 3/16	1 1/2	3 5/8	5 5/8
5 1/2	5 1/2	6 1/4	1	5 1/2-12	**	5 1/4-12	4-12	5 27/64	3 15/16	1 7/8	4 3/8	6 1/4
7	7	8	1	7-12	**	6 1/2-12	5 1/2-12	6 27/64	4 1/16	2	5 3/4	6 1/2

* Distance across wrench flats.





** (4) Spanner holes 33/64" x 1/2" deep.

Note: Other rod sizes available. Consult factory.

▲ Rod end style KK₂ is studded as standard for 5/8" and 1" diameter rods.

Studded rod end style is available for all rod sizes.

■ See page 105 for Series MN piston rod end styles.



CAUTION: When ordering replacement cylinders for competitive brands, our Style #1 rod ends may not be interchangeable with other manufacturers' Style #1. Our Style #2 should be used if this applies to your application.